

# OK-SEE 9000 SERIES

## TECHNICAL SPEC SHEET

Dimension& Weight:		
OKSEE-9000	Dimensions (mm)	Weight (kg)
	3850*1750*2300	1300kg
Warranty		
1 Year		
System Parameter:		
Run Time(150watts load)	70 hours	
Charge Time	8 hours	
System Voltage	DC24V	
Wind Rating Speed	45m/s	
Protection Level	IP65	
Solar System:		
No. of Solar Panel	3	
Panel Wattage	380W	
Panel Output	1140W	
Panel Material	Monocrystal Silicon	
Solar Controller	MPPT Solar Charge Controller	
Battery:		
No. of Battery	6 x 150Ah	
Capacity	450AH, DC24V	
Material	Gel Type Lead Acid	
Battery Life	50,000 hours	
Operational Temperature	-25~60°C	
Solar Panel		
Brand	JINKO	
Power	3PCS,380W	
Dimension& Weight:	1956*992*40mm,22.5KG	
Module Efficiency	20.5%	
Operational Temperature	-40~85°C	
Telescopic Mast:		
Type	Electric Mast	
Stage	5	
Material	Galvanized Steel	
Extended Height	20ft	
Operate for Extend and Lower	Electric winch Operation	
Max Payload	50KG	
Spiral Cable	2*cat6+4*18gauge	
Winch type	4500LBS,24VDC	
AC Charger:		
Main Supply Charger	110VAC input,40A	
Trailer:		
Type	Single Axle	
Brake	Electrical brake	
Fire Extinguisher	Included	
Tire size	215/75 R15	
Paint	Hot dip galvanized,then Powder coat twice	
Tow Hitch	50mm ball hitch	
Draw Bar Type	Folded	
Maximum load of trailer	2,000KG	
Certificate:		
Certificate:	CE,ISO9001,DOT Approved	

